


Last information update: June 2018



recessed luminaire Ø 137 - warm white passive dissipation LED - integrated DALI control gear - wide flood

Product code
Q194

Technical description

recessed adjustable removable luminaire for LED lamp with passive heat dissipation system. Structure with die-cast aluminium frame and main body; shaped surface with high level radiant effect for effectively reducing the temperature and keeping the long-term LED lamp performance unchanged. Steel rotation hinge, chrome-plated aluminium body closing ring. Reflector with high efficiency super-pure aluminium optic - wide flood beam angle. Body adjusted using manually operated device: internal 30° - external 75° - rotation about axis 355°. Supplied with DALI dimmable control gear connected to the luminaire. Warm white high efficiency LED.

Installation

recessed using steel springs in false ceilings with thicknesses starting at 1 mm; preparation hole Ø 125

Dimension (mm)
Ø137x91

Colour
White/Aluminium (39) | Grey/Aluminium (78)

Weight (Kg)
1.02

Mounting
ceiling recessed

Wiring
on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations



IP20

**Product configuration: Q194****Product characteristics**

Total lighting output [Lm]: 2338
Total power [W]: 24.6
Luminous efficacy [Lm/W]: 95
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 78
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 22
Nominal luminous [Lm]: 3000
Lamp maximum intensity [cd]: /
Beam angle [°]: 54°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 2.6
Colour temperature [K]: 3000
CRI: 80
Wavelength [nm]: /
MacAdam Step: 2


Polar

Imax=3107 cd		CIE		Lux			
90°	180°	nL 0.78		h	d	Em	Emax
		97-100-100-100-78		2	2	600	773
		UGR 19.9-19.9		4	4.1	150	193
		DIN A.61		6	6.1	67	86
		UTE 0.78A+0.00T		8	8.2	38	48
		F*1=965					
		F*1+F*2=997					
		F*1+F*2+F*3=1000					
α=54°							

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	69	65	63	60	65	62	62	59	76
1.0	72	69	66	65	68	66	66	63	81
1.5	76	74	72	70	73	71	70	68	87
2.0	79	77	75	74	76	75	74	71	92
2.5	80	79	78	77	78	77	76	74	95
3.0	81	80	80	79	79	78	77	75	97
4.0	83	82	81	81	80	80	79	77	98
5.0	83	82	82	82	81	81	79	78	99

Luminance curve limit



UGR diagram

Corrected UGR values (at 3000 lm bare lamp luminous flux)													
Reflect.:													
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30		
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30		
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20		
Room dim		viewed						viewed					
x	y	crosswise						endwise					
2H	2H	20.5	21.1	20.8	21.3	21.6	20.5	21.1	20.8	21.3	21.6		
	3H	20.3	20.9	20.7	21.2	21.5	20.3	20.9	20.7	21.2	21.5		
	4H	20.3	20.8	20.6	21.1	21.4	20.3	20.8	20.6	21.1	21.4		
	6H	20.2	20.7	20.5	21.0	21.3	20.2	20.7	20.5	21.0	21.3		
	8H	20.2	20.6	20.5	20.9	21.3	20.2	20.6	20.5	20.9	21.3		
	12H	20.1	20.6	20.5	20.9	21.3	20.1	20.6	20.5	20.9	21.3		
4H	2H	20.3	20.8	20.6	21.1	21.4	20.3	20.8	20.6	21.1	21.4		
	3H	20.1	20.6	20.5	20.9	21.3	20.1	20.6	20.5	20.9	21.3		
	4H	20.0	20.4	20.4	20.8	21.2	20.0	20.4	20.4	20.8	21.2		
	6H	20.0	20.3	20.4	20.7	21.1	20.0	20.3	20.4	20.7	21.1		
	8H	19.9	20.2	20.4	20.6	21.1	19.9	20.2	20.4	20.6	21.1		
	12H	19.9	20.1	20.3	20.6	21.0	19.9	20.1	20.3	20.6	21.0		
8H	4H	19.9	20.2	20.4	20.6	21.1	19.9	20.2	20.4	20.6	21.1		
	6H	19.8	20.1	20.3	20.5	21.0	19.8	20.1	20.3	20.5	21.0		
	8H	19.8	20.0	20.3	20.5	21.0	19.8	20.0	20.3	20.5	21.0		
	12H	19.7	19.9	20.2	20.4	20.9	19.7	19.9	20.2	20.4	20.9		
12H	4H	19.9	20.1	20.3	20.6	21.0	19.9	20.1	20.3	20.6	21.0		
	6H	19.8	20.0	20.3	20.5	21.0	19.8	20.0	20.3	20.5	21.0		
	8H	19.7	19.9	20.2	20.4	20.9	19.7	19.9	20.2	20.4	20.9		
Variations with the observer position at spacing:													
S =	1.0H	5.1 / -13.5						5.1 / -13.5					
	1.5H	7.9 / -14.7						7.9 / -14.7					
	2.0H	9.9 / -15.9						9.9 / -15.9					