


View Opti Beam Lens rotondo

Design iGuzzini / Arup

iGuzzini

Last information update: May 2018



round large body spotlight - super spot

Product code

Q306

Technical description

Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Neutral White tone 4000K LEDs with OPTIBEAM LENS technology and a well-defined super spot light beam. Dimmable DALI driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, an elliptical distribution refractor, a louver, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

Installation

On a three-phase/DALI electrified track

Dimension (mm)

Ø156x194

Colour

Black (04) | Black/White (47)

Weight (Kg)

1.66

Mounting

dali track|three circuit track

Wiring

Product complete with DALI dimmable components, housed in a semi-hidden box on the track.

Complies with EN60598-1 and pertinent regulations



IP20



Product configuration: Q306

Product characteristics

Total lighting output [Lm]: 632.5
Total power [W]: 16.8
Luminous efficacy [Lm/W]: 37.6
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 55
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 12
Nominal luminous [Lm]: 1150
Lamp maximum intensity [cd]: /
Beam angle [°]: 4°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 4.8
Colour temperature [K]: 4000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: 2

$I_{\max}=48336 \text{ cd}$	C0-180		Lux				
	h	d1	d2	Em	Emax		
	2	0.1	0.1	9612	12084		
	4	0.3	0.3	2403	3021		
	6	0.4	0.4	1068	1343		
	8	0.6	0.6	601	755		
$\alpha = 4^\circ$							

R	77	75	73	71	55	53	33	00	DRR
K0.8	49	46	44	42	45	44	43	41	75
1.0	51	48	47	45	48	46	46	44	80
1.5	54	52	50	49	51	50	49	48	86
2.0	56	54	53	52	53	52	52	50	91
2.5	57	56	55	54	55	54	53	52	94
3.0	57	57	56	55	56	55	54	53	96
4.0	58	58	57	57	57	56	55	54	98
5.0	59	58	58	58	57	57	56	55	99

QC	A	G	1.15	2000	1000	500	<~300	<~300	<~300
	B		1.50	2000	1000	750	500	<~300	<~300
	C		1.85	2000	1000	1000	500	<~300	<~300

85°
75°
65°
55°
45°

10² 2 3 4 5 6 8 10³ 2 3 4 5 6 8 10⁴ cd/m²

C0-180 C90-270