

## View Opti Beam Lens quadrato

Design iGuzzini / Arup

iGuzzini

Last information update: May 2018



### square small body spotlight - medium

#### Product code

Q333

#### Technical description


Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Warm White tone 3000K CRI90 LEDs with OPTIBEAM LENS technology and a well-defined spot light beam. Dimmable DALI driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, an elliptical distribution refractor, a louver, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

#### Installation

On a three-phase/DALI electrified track

#### Dimension (mm)

126x126x163



#### Colour

Black (04) | Black/White (47)

#### Weight (Kg)

1.13

#### Mounting

dali track|three circuit track

#### Wiring

Product complete with DALI dimmable components, housed in a semi-hidden box on the track.

Complies with EN60598-1 and pertinent regulations



IP20



pending

#### Product configuration: Q333

#### Product characteristics

Total lighting output [Lm]: 1591.6  
Total power [W]: 21.3  
Luminous efficacy [Lm/W]: 74.7  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 84  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 18  
Nominal luminous [Lm]: 1900  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 26°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 3.3  
Colour temperature [K]: 3000  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 2

**Polar**



**Isolux**

