


Last information update: May 2018

**Frame Angular Module - Down Office / Working UGR < 19 - Neutral LED****Product code**

Q436

**Technical description**

Angular element for Frame version profiles with contact frame; including a Neutral LED module. Microprismatic screen for controlled luminance emission UGR < 19 - 3000 cd/m<sup>2</sup> (working lighting); screen set up for connecting several lengths by overlapping. Integrated control gear. Pass-through wiring for continuous lines:

**Installation**

Recessed using the brackets on the profile.

**Dimension (mm)**

658x658x105

**Colour**

White (01) | Aluminium (12)

**Weight (Kg)**

5.1

**Mounting**

ceiling recessed

**Wiring**

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated electronic control gear.

**Notes**

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each side of the corner.

Complies with EN60598-1 and pertinent regulations



IP20

**Product configuration: Q436****Product characteristics**

Total lighting output [Lm]: 1943.7  
Total power [W]: 16.1  
Luminous efficacy [Lm/W]: 120.7  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 2

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 72  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 7.1  
Nominal luminous [Lm]: 1350  
Lamp maximum intensity [cd]: /  
Beam angle [°]: /

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 1  
Colour temperature [K]: 4000  
CRI: 80  
Wavelength [Nm]: /  
MacAdam Step: 3

Polar

