



Last information update: May 2018

**Frame Angular Module - Down Office / Working UGR < 19 - Warm LED - DALI****Product code**

Q439

**Technical description**

Angular element for Frame version profiles with contact frame; including a Warm LED module. Microprismatic screen for controlled luminance emission UGR < 19 - 3000 cd/m<sup>2</sup> (working lighting); screen set up for connecting several lengths by overlapping. Built-in DALI dimmable control gear. Pass-through wiring for continuous lines:

**Installation**

Recessed using the brackets on the profile.

**Dimension (mm)**

658x658x105

**Colour**

White (01) | Aluminium (12)

**Weight (Kg)**

5.1

**Mounting**

ceiling recessed

**Wiring**

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated dimmable DALI control gear.

**Notes**

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each side of the corner.

Complies with EN60598-1 and pertinent regulations



IP20



pending

**Product configuration: Q439****Product characteristics**

Total lighting output [Lm]: 1799.8

Total power [W]: 14.2

Luminous efficacy [Lm/W]: 126.7

Number of optical assemblies: 2

Total luminous flux at or above an angle of 90° [Lm]: 0

Emergency luminous flux [Lm]: /

Voltage [V]: -

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 72

Lamp code: LED

ZVEI Code: LED

Nominal power [W]: 7.1

Nominal luminous [Lm]: 1250

Lamp maximum intensity [cd]: /

Beam angle [°]: /

Number of lamps for optical assembly: 1

Socket: /

Ballast losses [W]: 0

Colour temperature [K]: 3000

CRI: 80

Wavelength [Nm]: /

MacAdam Step: 3

Polar

