


Last information update: June 2018



### Frame 3 cells - Medium beam - LED

#### Product code

Q473

#### Technical description

Linear miniaturised recessed luminaire with 3 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast zamak radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Ballast not included, available with separate code.

#### Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 60.

#### Dimension (mm)

64x28x50

#### Colour

White (01) | White/Brass (41) | Black/Black (43) | Black/White (47) | Grey/Black (74) | (E7)

#### Weight (Kg)

0.15

#### Mounting

wall recessed|ceiling recessed

#### Wiring

Direct current ballasts to be ordered separately: ON-OFF - code no. MXF9 (min 1 / max 2); dimmable DALI - code no. BZM4 (min 1 / max 6) - check the instruction sheet for the lengths and compatible cross-sections of the cables to be used.

#### Notes

.

Complies with EN60598-1 and pertinent regulations



IP20



#### Product configuration: Q473

#### Product characteristics

Total lighting output [Lm]: 356  
Total power [W]: 5.9  
Luminous efficacy [Lm/W]: 60.3  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 79  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 5.9  
Nominal luminous [Lm]: 450  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 24°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 0  
Colour temperature [K]: 2700  
CRI: 90  
Wavelength [nm]: /  
MacAdam Step: 3

	<b>CIE</b> nL 0.79 100-100-100-100-79 UGR <10<10 <b>DIN</b> A.61 <b>UTE</b> 0.79A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000 <b>CIBSE</b> LG3 Lc500 cd/m <sup>2</sup> at 65°	<b>Lux</b>			
		<b>h</b>	<b>d</b>	<b>Em</b>	<b>E<sub>max</sub></b>
	2	0.9	341	411	
	4	1.7	85	103	
	6	2.6	38	46	
8	3.4	21	26		

R	77	75	73	71	55	53	33	00	DDR
K0.8	71	68	65	63	67	65	64	62	78
1.0	75	71	69	67	70	68	68	66	83
1.5	78	76	74	72	75	73	72	70	89
2.0	81	79	77	76	78	76	76	73	93
2.5	82	81	80	79	80	79	78	76	96
3.0	83	82	81	81	81	80	79	77	98
4.0	84	83	83	82	82	82	80	79	99
5.0	84	84	84	83	83	82	81	79	100

The graph plots viewing angle  $\alpha_h$  (in degrees) on the y-axis (45° to 85°) against luminance  $cd/m^2$  on the x-axis (logarithmic scale,  $10^2$  to  $10^4$ ). A red dashed line indicates the viewing angle range for C0-180 and C90-270. The graph is divided into two sections: C0-180 (left) and C90-270 (right). The top section shows the relationship for different camera models (QC, A, G, B, C) and distances (1.15, 1.50, 1.85). The bottom section shows the relationship for different camera models (QC, A, G, B, C) and distances (1.15, 1.50, 1.85).

# UGR diagram

Corrected UGR values (at 450 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	2.4	4.5	2.7	4.8	5.1	2.4	4.5	2.7	4.8	5.1
	3H	2.2	3.8	2.6	4.1	4.5	2.2	3.8	2.6	4.1	4.5
	4H	2.1	3.5	2.5	3.8	4.2	2.1	3.5	2.5	3.8	4.2
	6H	2.1	3.1	2.5	3.5	3.8	2.1	3.1	2.5	3.5	3.8
	8H	2.1	3.1	2.5	3.4	3.8	2.1	3.1	2.4	3.4	3.8
	12H	2.0	3.1	2.4	3.4	3.8	2.0	3.0	2.4	3.4	3.8
4H	2H	2.1	3.5	2.5	3.8	4.2	2.1	3.5	2.5	3.8	4.2
	3H	2.0	3.0	2.4	3.4	3.8	2.0	3.0	2.4	3.4	3.8
	4H	1.9	2.9	2.3	3.3	3.7	1.9	2.9	2.3	3.3	3.7
	6H	1.5	3.2	2.0	3.7	4.1	1.5	3.2	2.0	3.7	4.1
	8H	1.4	3.3	1.9	3.8	4.3	1.4	3.3	1.9	3.8	4.3
	12H	1.3	3.3	1.8	3.8	4.3	1.3	3.3	1.8	3.7	4.3
8H	4H	1.4	3.3	1.9	3.8	4.3	1.4	3.3	1.9	3.8	4.3
	6H	1.3	3.1	1.8	3.6	4.1	1.3	3.1	1.8	3.6	4.1
	8H	1.3	2.9	1.8	3.4	3.9	1.3	2.9	1.8	3.4	3.9
	12H	1.5	2.5	2.0	3.0	3.5	1.5	2.5	2.0	3.0	3.5
12H	4H	1.3	3.3	1.8	3.7	4.3	1.3	3.3	1.8	3.8	4.3
	6H	1.3	2.9	1.8	3.4	3.9	1.3	2.9	1.9	3.4	3.9
	8H	1.5	2.5	2.0	3.0	3.5	1.5	2.5	2.0	3.0	3.5
Variations with the observer position at spacing:											
S =		1.0H	6.9 / -11.5					6.9 / -11.5			
		1.5H	9.7 / -11.7					9.7 / -11.7			
		2.0H	11.7 / -11.8					11.7 / -11.8			