


Last information update: June 2018



Frame 15 cells - Wideflood beam - LED

Product code

Q515

Technical description

Linear miniaturised recessed luminaire with 15 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with a power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 276.

Dimension (mm)

280x28x50

Colour

White (01) | White/Brass (41) | Black/Black (43) | Black/White (47) | Grey/Black (74) | (E7)

Weight (Kg)

0.75

Mounting

wall recessed|ceiling recessed

Wiring

On the power supply unit with terminal board included.

Notes

.

Complies with EN60598-1 and pertinent regulations



IP20



Product configuration: Q515

Product characteristics

Total lighting output [Lm]: 2158
Total power [W]: 33
Luminous efficacy [Lm/W]: 65.4
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: 230
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 83
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 29
Nominal luminous [Lm]: 2600
Lamp maximum intensity [cd]: /
Beam angle [°]: 58°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 4
Colour temperature [K]: 4000
CRI: 90
Wavelength [nm]: /
MacAdam Step: 3

	I max=2750 cd 90° 180° 90° 3000 0° α =58°	CIE nL 0.83 100-100-100-100-83 UGR 16.2-16.2 DIN A.61 UTE 0.83A+0.00T F*1=996 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 Lc500 cd/m² at 65°	Lux <table border="1"> <thead> <tr> <th>h</th> <th>d</th> <th>Em</th> <th>E_{max}</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>2.2</td> <td>547</td> <td>682</td> </tr> <tr> <td>4</td> <td>4.4</td> <td>137</td> <td>170</td> </tr> <tr> <td>6</td> <td>6.7</td> <td>61</td> <td>76</td> </tr> <tr> <td>8</td> <td>8.9</td> <td>34</td> <td>43</td> </tr> </tbody> </table>	h	d	Em	E _{max}	2	2.2	547	682	4	4.4	137	170	6	6.7	61	76	8	8.9	34	43
	h	d	Em	E _{max}																			
	2	2.2	547	682																			
	4	4.4	137	170																			
	6	6.7	61	76																			
8	8.9	34	43																				

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	78	77	76	73	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

QC	A	G	1.15	2000	1000	500	<=300	<=300	<=300
B			1.50		2000	1000	750	500	<=300
C			1.85			2000		1000	500

The graph shows two sets of curves for different surface types (A, B, C) and distances (1.15, 1.50, 1.85). The curves for C0-180 are solid lines, and the curves for C90-270 are dashed lines. The curves for C0-180 show a higher angle of reflection (αh) for a given incident radiation dose compared to the curves for C90-270. The curves for C0-180 are labeled with values 85°, 75°, 65°, 55°, and 45°. The curves for C90-270 are labeled with values 8, 6, 4, 2, and 0. The curves for C0-180 are labeled with values 10², 2, 3, 4, 5, 6, 8, 10³, and 10⁴. The curves for C90-270 are labeled with values 10², 2, 3, 4, 5, 6, 8, 10³, and 10⁴. The curves for C0-180 are labeled with values 10², 2, 3, 4, 5, 6, 8, 10³, and 10⁴. The curves for C90-270 are labeled with values 10², 2, 3, 4, 5, 6, 8, 10³, and 10⁴.

UGR diagram

Corrected UGR values (at 2000 lm bare lamp luminous flux)												
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise					
2H	2H	16.8	17.3	17.1	17.5	17.7	16.8	17.3	17.1	17.5	17.7	
	3H	16.7	17.1	17.0	17.3	17.6	16.7	17.1	17.0	17.3	17.6	
	4H	16.6	17.0	16.9	17.3	17.6	16.6	17.0	16.9	17.3	17.6	
	6H	16.5	16.9	16.9	17.2	17.5	16.5	16.9	16.9	17.2	17.5	
	8H	16.5	16.8	16.8	17.2	17.5	16.5	16.8	16.8	17.2	17.5	
	12H	16.4	16.8	16.8	17.1	17.5	16.4	16.8	16.8	17.1	17.5	
4H	2H	16.6	17.0	16.9	17.3	17.6	16.6	17.0	16.9	17.3	17.6	
	3H	16.4	16.8	16.8	17.1	17.5	16.4	16.8	16.8	17.1	17.5	
	4H	16.3	16.6	16.7	17.0	17.4	16.3	16.6	16.7	17.0	17.4	
	6H	16.3	16.5	16.7	16.9	17.3	16.3	16.5	16.7	16.9	17.3	
	8H	16.2	16.5	16.7	16.9	17.3	16.2	16.5	16.6	16.9	17.3	
	12H	16.2	16.4	16.6	16.8	17.3	16.2	16.4	16.6	16.8	17.3	
8H	4H	16.2	16.5	16.6	16.9	17.3	16.2	16.5	16.7	16.9	17.3	
	6H	16.1	16.3	16.6	16.8	17.2	16.1	16.3	16.6	16.8	17.2	
	8H	16.1	16.2	16.5	16.7	17.2	16.1	16.2	16.5	16.7	17.2	
	12H	16.0	16.2	16.5	16.6	17.2	16.0	16.2	16.5	16.6	17.2	
12H	4H	16.2	16.4	16.6	16.8	17.3	16.2	16.4	16.6	16.8	17.3	
	6H	16.1	16.2	16.5	16.7	17.2	16.1	16.2	16.5	16.7	17.2	
	8H	16.0	16.2	16.5	16.6	17.2	16.0	16.2	16.5	16.6	17.2	
Variations with the observer position at spacing:												
S =		1.0H	6.5 / -24.9					6.5 / -24.9				
		1.5H	9.4 / -25.6					9.4 / -25.6				
		2.0H	11.4 / -25.8					11.4 / -25.8				