


## Laser Blade XS

Design iGuzzini

iGuzzini

Last information update: June 2018



### Frame 15 cells - Flood beam - LED

#### Product code

Q517

#### Technical description

Linear miniaturised recessed luminaire with 15 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with DALI power supply unit connected to the luminaire.

#### Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 276.

#### Dimension (mm)

280x28x50

#### Colour

White (01) | White/Brass (41) | Black/Black (43) | Black/White (47) | Grey/Black (74) | (E7)

#### Weight (Kg)

0.75

#### Mounting

wall recessed|ceiling recessed

#### Wiring

On the power supply unit with terminal board included.

#### Notes

.

Complies with EN60598-1 and pertinent regulations



IP20



#### Product configuration: Q517

#### Product characteristics

Total lighting output [Lm]: 1909  
Total power [W]: 33  
Luminous efficacy [Lm/W]: 57.8  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: 230  
Number of optical assemblies: 1

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 83  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 29  
Nominal luminous [Lm]: 2300  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 42°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 4  
Colour temperature [K]: 3000  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 3

	<b>Imax=3921 cd</b> <b>CIE</b> nL 0.83 100-100-100-100-83 UGR <10<10 <b>DIN</b> A.61 <b>UTE</b> 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000 <b>CIBSE</b> LG3 L<500 cd/m² at 65°	<b>Lux</b>			
		<b>h</b>	<b>d</b>	<b>Em</b>	<b>E<sub>max</sub></b>
		2	1.5	798	973
		4	3.1	199	243
		6	4.6	89	108
<b>α = 42°</b>		8	6.1	50	61

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	80	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	87	85	83	100

QC

A	G	1.15	2000	1000	500	<=300	<=300	<=300
B		1.50		2000	1000	750	500	<=300
C		1.85			2000		1000	500

85°  
75°  
65°  
55°  
45°

10<sup>2</sup> 2 4 5 8 10<sup>3</sup> 2 3 4 5 6 8 10<sup>4</sup> cd/m<sup>2</sup>

C0-180 C90-270

# UGR diagram

Corrected UGR values (at 2300 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	6.6	7.1	6.9	7.3	7.5	6.6	7.1	6.9	7.3	7.5
	3H	6.5	6.9	6.8	7.2	7.4	6.5	6.9	6.8	7.2	7.4
	4H	6.4	6.8	6.7	7.1	7.4	6.4	6.8	6.7	7.1	7.4
	6H	6.3	6.7	6.7	7.0	7.3	6.3	6.7	6.7	7.0	7.3
	8H	6.3	6.6	6.6	7.0	7.3	6.3	6.6	6.6	7.0	7.3
	12H	6.3	6.6	6.6	6.9	7.3	6.2	6.6	6.6	6.9	7.3
4H	2H	6.4	6.8	6.7	7.1	7.4	6.4	6.8	6.7	7.1	7.4
	3H	6.2	6.6	6.6	6.9	7.3	6.2	6.6	6.6	6.9	7.3
	4H	6.1	6.5	6.5	6.8	7.2	6.1	6.5	6.5	6.8	7.2
	6H	6.1	6.3	6.5	6.7	7.1	6.1	6.3	6.5	6.7	7.1
	8H	6.0	6.3	6.5	6.7	7.1	6.0	6.3	6.5	6.7	7.1
	12H	6.0	6.2	6.4	6.6	7.1	6.0	6.2	6.4	6.6	7.1
8H	4H	6.0	6.3	6.5	6.7	7.1	6.0	6.3	6.5	6.7	7.1
	6H	5.9	6.1	6.4	6.6	7.1	5.9	6.1	6.4	6.6	7.1
	8H	5.9	6.1	6.4	6.5	7.0	5.9	6.1	6.4	6.5	7.0
	12H	5.8	6.0	6.3	6.5	7.0	5.8	6.0	6.3	6.5	7.0
12H	4H	6.0	6.2	6.4	6.6	7.1	6.0	6.2	6.4	6.6	7.1
	6H	5.9	6.0	6.4	6.5	7.0	5.9	6.1	6.4	6.5	7.0
	8H	5.8	6.0	6.3	6.5	7.0	5.8	6.0	6.3	6.5	7.0
Variations with the observer position at spacing:											
S =		1.0H	7.0 / -14.5					7.0 / -14.5			
		1.5H	9.8 / -14.7					9.8 / -14.7			
		2.0H	11.8 / -14.8					11.8 / -14.8			