


Last information update: June 2018

**Minimal 15 cells - Flood beam - LED****Product code**


Q576

**Technical description**

Linear miniaturised recessed luminaire with 15 optical elements for LED lamps - fixed optic. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast zamak radiant surface, minimal (frameless) version for mounting flush with the ceiling. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with DALI power supply unit connected to the luminaire.

**Installation**

Recessed with steel wire springs on the specific adapter (included) which allows flush-mounting with the ceiling. Adapter fixed to false ceiling (compatible thicknesses of 12.5 / 15 / 20 mm) with screws; subsequent filling and smoothing operations; insertion of luminaire body and aesthetic end finishing. A special protective sheath allows finishing operations on the plasterboard to be simplified and speeded up. Preparation hole 28 x 274.

**Dimension (mm)**

272x25x50

**Colour**

White (01) | Black (04) | Brass (14) | (E6)

**Weight (Kg)**

0.7

**Mounting**

wall recessed|ceiling recessed

**Wiring**

On the power supply unit with terminal board included.

**Notes**

The special steel wire spring provided is required to facilitate the eventual extraction of the recessed body once it has been inserted.

Complies with EN60598-1 and pertinent regulations



pending

**Product configuration: Q576****Product characteristics**

Total lighting output [Lm]: 2117  
Total power [W]: 33  
Luminous efficacy [Lm/W]: 64.1  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: 230  
Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 83  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 29  
Nominal luminous [Lm]: 2550  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 42°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 4  
Colour temperature [K]: 4000  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 3


**Polar**

	<b>Imax</b> =4347 cd 90° 180° 90° 4000 0° α=42°	<b>CIE</b> nL 0.83 100-100-100-100-83 UGR <10-<10 <b>DIN</b> A.61 <b>UTE</b> 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000 <b>CIBSE</b> LG3 L<500 cd/m <sup>2</sup> at 65°	<b>Lux</b> h d Em Emax 2 1.5 885 1079 4 3.1 221 270 6 4.6 98 120 8 6.1 55 67
--	---	--	---

**Utilisation factors**

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	80	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	87	85	83	100

**Luminance curve limit**



**UGR diagram**

Corrected UGR values (at 2550 lm bare lamp luminous flux)											
Reflect.:											
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed					viewed				
x	y	crosswise					endwise				
2H	2H	6.9	7.4	7.2	7.7	7.9	6.9	7.4	7.2	7.7	7.9
	3H	6.8	7.3	7.1	7.5	7.8	6.8	7.3	7.1	7.5	7.8
	4H	6.8	7.2	7.1	7.4	7.7	6.7	7.2	7.1	7.4	7.7
	6H	6.7	7.0	7.0	7.4	7.7	6.7	7.0	7.0	7.4	7.7
	8H	6.6	7.0	7.0	7.3	7.7	6.6	7.0	7.0	7.3	7.7
	12H	6.6	7.0	7.0	7.3	7.6	6.6	6.9	7.0	7.3	7.6
4H	2H	6.7	7.2	7.1	7.4	7.7	6.8	7.2	7.1	7.4	7.7
	3H	6.6	6.9	7.0	7.3	7.6	6.6	6.9	7.0	7.3	7.6
	4H	6.5	6.8	6.9	7.2	7.6	6.5	6.8	6.9	7.2	7.6
	6H	6.4	6.7	6.8	7.1	7.5	6.4	6.7	6.8	7.1	7.5
	8H	6.4	6.6	6.8	7.0	7.5	6.4	6.6	6.8	7.0	7.5
	12H	6.3	6.6	6.8	7.0	7.5	6.3	6.5	6.8	7.0	7.4
8H	4H	6.4	6.6	6.8	7.0	7.5	6.4	6.6	6.8	7.0	7.5
	6H	6.3	6.5	6.8	6.9	7.4	6.3	6.5	6.8	6.9	7.4
	8H	6.2	6.4	6.7	6.9	7.4	6.2	6.4	6.7	6.9	7.4
	12H	6.2	6.4	6.7	6.8	7.4	6.2	6.3	6.7	6.8	7.3
12H	4H	6.3	6.5	6.8	7.0	7.4	6.3	6.6	6.8	7.0	7.5
	6H	6.2	6.4	6.7	6.9	7.4	6.2	6.4	6.7	6.9	7.4
	8H	6.2	6.3	6.7	6.8	7.3	6.2	6.4	6.7	6.8	7.4
Variations with the observer position at spacing:											
S =	1.0H	7.0 / -14.5				7.0 / -14.5					
	1.5H	9.8 / -14.7				9.8 / -14.7					
	2.0H	11.8 / -14.8				11.8 / -14.8					