


Last information update: May 2018



**Palco LV spotlight 2 x Ø 19 - spot beam**

**Product code**

Q626

**Technical description**


Lighting assembly consisting of two miniaturised adjustable spotlights with adapter for installation on 48V low voltage track. Spotlight bodies made of die-cast zamak with a passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each spotlight mounted on the track to be regulated separately. In the model where the spotlights are mounted in pairs, any regulations are applied to both of them. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

**Installation**

Mechanical fastening with adapter on track.

**Dimension (mm)**

Ø19



**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.09

**Mounting**

Low voltage track

**Wiring**

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



**Product configuration: Q626**

**Product characteristics**

Total lighting output [Lm]: 195.2  
 Total power [W]: 5.4  
 Luminous efficacy [Lm/W]: 36.1  
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 2

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 61  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 2  
 Nominal luminous [Lm]: 160  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 14°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 0.7  
 Colour temperature [K]: 3000  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 3

**Polar**

