iGuzzini

Last information update: May 2018

Palco LV spotlight 2 x Ø 19 - spot beam



Product code

Q628

#### Technical description

Lighting assembly consisting of two miniaturised adjustable spotlights with adapter for installation on 48V low voltage track. Spotlight bodies made of die-cast zamak with a passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated "power line" technology allows each spotlight mounted on the track to be regulated separately. In the model where the spotlights are mounted in pairs, any regulations are applied to both of them. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.



#### Installation

Mechanical fastening with adapter on track.

## Dimension (mm)

Ø19

#### Colour

White (01) | Black (04)

## Weight (Kg)

0.09

## Mounting

Low voltage track

## Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations















# Product configuration: Q628

## **Product characteristics**

Total lighting output [Lm]: 183 Total power [W]: 5.4

Luminous efficacy [Lm/W]: 33.9

Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0

Emergency luminous flux [Lm]: / Voltage [V]: -

Number of optical assemblies: 2

## Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 61

Lamp code: LED ZVEI Code: LED Nominal power [W]: 2 Nominal luminous [Lm]: 150 Lamp maximum intensity [cd]: /

Beam angle [°]: 14°

Number of lamps for optical assembly: 1

Socket: /

Ballast losses [W]: 0.7 Colour temperature [K]: 2700

CRI: 90

Wavelength [Nm]: / MacAdam Step: 3

## Polar

Imax=1101 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	1	0.2	833	1101
	2	0.5	208	275
1000	3	0.7	93	122
α=14°	4	1	52	69