Design Artec3 Studio

iGuzzini

Last information update: May 2018

### Palco LV spotlight Ø 19 - horizontal rod - medium beam

Product code Q642




#### Technical description

Miniaturised adjustable spotlight with a cantilever horizontal rod. This solution is ideal for lighting paintings and vertical surfaces efficiently. Adapter for a 48V low voltage track integrated in a die-cast zamak structure with a safety system for securing it to the track. Aluminium support rod with adjustable  $-10^{\circ}$  /  $+45^{\circ}$  tilting and mechanical locking. The swivel joint at the end of the rod allows the spotlight to be rotated horizontally by 90° in the opposite direction and tilted vertically by 0°  $\cdot$  90°. The optic unit is in a set back position with a plastic high definition lens. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each spotlight mounted on the track to be regulated separately.

# Installation

The structure is secured mechanically to the track with an adapter and a "turn & block" safety system.



## Dimension (mm) Ø19

Colour White (01) | Black (04)

Weight (Kg)

0.19

### Mounting

Low voltage track

## Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.



### Product configuration: Q642

#### Product characteristics

Total lighting output [Lm]: 107 Total power [W]: 3.4 Luminous efficacy [Lm/W]: 31.5 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

## Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 67 Lamp code: LED ZVEI Code: LED Nominal power [W]: 2 Nominal luminous [Lm]: 160 Lamp maximum intensity [cd]: / Beam angle [°]: 24° Total luminous flux at or above an angle of 90° [Lm]: 0 Emergency luminous flux [Lm]: / Voltage [V]: -

Complies with EN60598-1 and pertinent regulations

Number of optical assemblies: 1

Number of lamps for optical assembly: 1 Socket: / Ballast losses [W]: 1.4 Colour temperature [K]: 3000 CRI: 90 Wavelength [Nm]: / MacAdam Step: 3

