



Last information update: May 2018



**Ceiling-mounted LB XS Linear GL Pro - 10 cells - remote driver**

**Product code**

Q890

**Technical description**

Ceiling-mounted luminaire with 10 optic elements for LED lamps - fixed optics with metallised thermoplastic high definition Opti-Beam reflectors. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux optimised by a special diffuser screen that reduces direct glare significantly. Extruded aluminium main body and technical dissipation unit - shaped steel fixing plate. Ballast not included, available with separate code.

**Installation**

Ceiling-mounted with surface fixing plate (screws and screw anchors not included) - external locking system.

**Dimension (mm)**

184x27x50

**Colour**

White (01) | (F2)

**Weight (Kg)**

0.3

**Mounting**

ceiling surface

**Wiring**

Cables supplied with quick-coupling terminals for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



**Product configuration: Q890**

**Product characteristics**

Total lighting output [Lm]: 1208  
 Total power [W]: 19  
 Luminous efficacy [Lm/W]: 63.6  
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 69  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 19  
 Nominal luminous [Lm]: 1750  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: /

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 0  
 Colour temperature [K]: 4000  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 3

**Polar**



**Isolux**

