



Last information update: May 2018

**Ceiling-mounted Linear Wall Washer - remote driver****Product code**

Q897

**Technical description**

Ceiling-mounted linear luminaire for LED lamps. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an even efficient beam on the wall. Extruded aluminium main body and technical dissipation unit - shaped steel fixing plate. Ballast not included, available with separate code.

**Installation**

Ceiling-mounted with surface fixing plate (screws and screw anchors not included) - external locking system.

**Dimension (mm)**

184x27x50

**Colour**

Black/Black (43) | Black/White (47)

**Weight (Kg)**

0.3

**Mounting**

ceiling surface

**Wiring**

Cables supplied with quick-coupling terminals for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20

**Product configuration: Q897****Product characteristics**

Total lighting output [Lm]: 532  
 Total power [W]: 17  
 Luminous efficacy [Lm/W]: 31.3  
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 38  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 17  
 Nominal luminous [Lm]: 1400  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: /

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 0  
 Colour temperature [K]: 3000  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 3

Polar

