


Last information update: June 2018



Palco single recess Ø19 - medium - remote driver

Product code

QC13

Technical description

Miniaturised adjustable spotlight for recessed installation. Spotlight body with a cast zamak dissipation system and rotation units - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

Installation

Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø19 mm.

Dimension (mm)

Ø19

Colour

White (01) | Black (04)

Weight (Kg)

0.06


Mounting

wall recessed|ceiling recessed

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Product configuration: QC13

Product characteristics

Total lighting output [Lm]: 101
 Total power [W]: 2
 Luminous efficacy [Lm/W]: 50.3
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: -
 Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 67
 Lamp code: LED
 ZVEI Code: LED
 Nominal power [W]: 2
 Nominal luminous [Lm]: 150
 Lamp maximum intensity [cd]: /
 Beam angle [°]: 24°

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: 0
 Colour temperature [K]: 2700
 CRI: 90
 Wavelength [Nm]: /
 MacAdam Step: 3

Polar

