

Last information update: June 2018



**Palco linear recess 3 x Ø19 - medium - remote driver**

**Product code**

QC16

**Technical description**


Linear luminaire for recessed installation with 3 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - a linear recess structure consisting of an extruded aluminium internal profile, painted steel caps and stop plate - steel wire fixing springs. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

**Installation**

Recessed linear base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 00 x 000 mm. Option of installing next to linear versions so as to create a continuous line.

**Dimension (mm)**

Ø19



**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.06

**Mounting**

wall recessed|ceiling recessed

**Wiring**

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20



**Product configuration: QC16**

**Product characteristics**

Total lighting output [Lm]: 322  
 Total power [W]: 6  
 Luminous efficacy [Lm/W]: 53.6  
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 3

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 67  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 2  
 Nominal luminous [Lm]: 160  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 24°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 0  
 Colour temperature [K]: 3000  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 3

**Polar**

