

Last information update: June 2018



Palco linear recess 3 x Ø19 - medium - remote driver

Product code

QC17

Technical description


Linear luminaire for recessed installation with 3 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - a linear recess structure consisting of an extruded aluminium internal profile, painted steel caps and stop plate - steel wire fixing springs. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

Installation

Recessed linear base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 00 x 000 mm. Option of installing next to linear versions so as to create a continuous line.

Dimension (mm)

Ø19



Colour

White (01) | Black (04)

Weight (Kg)

0.06

Mounting

wall recessed|ceiling recessed

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20



Product configuration: QC17

Product characteristics

Total lighting output [Lm]: 302
 Total power [W]: 6
 Luminous efficacy [Lm/W]: 50.3
 Life Time: > 50,000h - L80 - B10 (Ta 25° C)

Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: -
 Number of optical assemblies: 3

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 67
 Lamp code: LED
 ZVEI Code: LED
 Nominal power [W]: 2
 Nominal luminous [Lm]: 150
 Lamp maximum intensity [cd]: /
 Beam angle [°]: 24°

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: 0
 Colour temperature [K]: 2700
 CRI: 90
 Wavelength [Nm]: /
 MacAdam Step: 3

Polar

