



Last information update: June 2018



**Palco single recess Ø51 - spot - remote driver**

**Product code**

QC28

**Technical description**

Miniaturised adjustable spotlight for recessed installation. Spotlight body with a die-cast aluminium dissipation system - cast zamak rotation unit - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

**Installation**

Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø36 mm.

**Dimension (mm)**

Ø51

**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.06

**Mounting**

wall recessed|ceiling recessed

**Wiring**

Output cables for connecting to power supply line.

**Notes**

Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



**Product configuration: QC28**

**Product characteristics**

Total lighting output [Lm]: 547  
 Total power [W]: 12  
 Luminous efficacy [Lm/W]: 45.6  
 Life Time: 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 72  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 12  
 Nominal luminous [Lm]: 760  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 12°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 0  
 Colour temperature [K]: 2700  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 3

**Polar**

