


Last information update: June 2018



Palco single surface Ø19 - medium - remote driver

Product code
QC34

Technical description

Miniaturised adjustable spotlight for surface installation. Spotlight body with a cast zamak dissipation system and rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

Installation

Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

Dimension (mm)

Ø19

Colour

White (01) | Black (04)

Weight (Kg)

0.06


Mounting

wall surface|ceiling surface

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Product configuration: QC34

Product characteristics

Total lighting output [Lm]: 107
Total power [W]: 2
Luminous efficacy [Lm/W]: 53.6
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 67
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 2
Nominal luminous [Lm]: 160
Lamp maximum intensity [cd]: /
Beam angle [°]: 24°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 0
Colour temperature [K]: 3000
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 3

Polar

