


Last information update: June 2018



## Palco linear surface 2 x Ø19 - medium - remote driver

### Product code

QC36

### Technical description

Linear luminaire for surface installation with 2 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - extruded aluminium linear surface structure - shaped steel fixing plate - extruded aluminium linear surface structure with mechanical coupling system - thermoplastic side end caps. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

### Installation

Installation surface plate fastening - structure attached using a mechanical locking mechanism - insertion of side end caps. This specific locking system can be installed next to linear versions so as to create a continuous external line.

### Dimension (mm)

Ø19

### Colour

White (01) | Black (04)

### Weight (Kg)

0.06

### Mounting

wall surface|ceiling surface

### Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20



### Product configuration: QC36

#### Product characteristics

Total lighting output [Lm]: 214  
Total power [W]: 4  
Luminous efficacy [Lm/W]: 53.6  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 2

#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 67  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 2  
Nominal luminous [Lm]: 160  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 24°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 0  
Colour temperature [K]: 3000  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 3

**Polar**

