


Last information update: June 2018



**Palco single surface Ø37 - spot - remote driver**

**Product code**  
QC42

**Technical description**

Miniaturised adjustable spotlight for surface installation. Spotlight body with a die-cast aluminium dissipation system - cast zamak rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

**Installation**

Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

**Dimension (mm)**

Ø37

**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.06

**Mounting**

wall surface|ceiling surface


**Wiring**

Output cables for connecting to power supply line.

**Notes**

Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



**Product configuration: QC42**

**Product characteristics**

Total lighting output [Lm]: 387  
Total power [W]: 7.2  
Luminous efficacy [Lm/W]: 53.7  
Life Time: 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 73  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 7.2  
Nominal luminous [Lm]: 530  
Lamp maximum intensity [cd]: /  
Beam angle [°]: 16°

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 0  
Colour temperature [K]: 2700  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 3

**Polar**