


SLIDE IP55 LED GE

Slide is one of the Modular icons. Its name refers to the light gliding out from the luminaire, channelled by the stunning inner body, and creating a softer and smooth lighting experience. Slide owes its popularity to its deeply embedded light source. It is available in the Modular donkey grey structure with black inner body or in an entirely white structure version.

Art. Nr. 10486174

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 92 h 75	
Weight	0.3kg	
Min. Distance	0.1	
IP	IP55	
Glow Wire Test	960°	
CRI	90	
Power supply	350mA 16.5Vf	500mA 17.1Vf
Connected load	6.2W	9.2W
Lumen	324lm	416lm
Efficacy	52lm/W	45lm/W
UGR	6	7
Adjustability	Not Applicable	
Remark	! 3500K and 4000K on request	



This label is available in other languages:
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	MEDIUM 25°	MEDIUM 25°
donkey grey struc	10486174	10486374
white struc	10486109	10486309



SLIDE IP55 LED GE

ACCESSORIES

HUE-BRIDGE

70000617	PHILIPS HUE BRIDGE UK
70000616	PHILIPS HUE BRIDGE EU

HUE-DEVICE

70000614	PHILIPS HUE DIMMER SWITCH
70000615	PHILIPS HUE TAP SWITCH
70000847	PHILIPS HUE SENSOR

HUE-MODULE

13190030	MODULAR CONNECTED 1-10V WHITE COMPONENT
----------	---

CONBOX

10889830	CONBOX 190X192X130X256
----------	------------------------

GYPKIT

12290330	GYPKIT 190X190 - Ø92
----------	----------------------