





FALL 1.3 IP54 LED GI

In Belgium, Modular's birthplace, the wind makes trees grow in odd angles alongside several canals. A strong image. Fall was inspired by this, although in a more minimalist shape. This exterior fixture is at a 10° angle and therefore seems to be bending slightly in the wind. The semi-transparent polycarbonate ensures diffused light. Available in various heights and colours. A ground stake is available for installation in soft ground.

PECIFICATIONS	
Lamp	1x LED-strip 24V 6W
Gear / Transfo	1X 225 3016 24V 3W
Weight	1.94kg
Min. Distance	0.1 m
Power supply	230V
IP	IP54
Glow Wire Test	960°
Lifetime	40000 hrs
CRI	80
Lumen	140 Lm
Efficacy	15 Lm/W
UGR	18
Adjustability	Not Applicable
MODULAR* This luminaire contains built-in LED lamps.	This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf
A' A B C D E	
The lamps cannot be changed in the luminaire.	
874/2012	ı

	WARM WHITE
	3000K / CRI 80+
black struc	11180632
white struc	11180609

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

FALL



FALL 1.3 IP54 LED GI			
ACCESSORIES			
EARTHPIN			
11189102	EARTHPIN H350 WITH SQUARE PLATE 100X100	_	
	•		