





FALL 1.1 IP54 LED GI

In Belgium, Modular's birthplace, the wind makes trees grow in odd angles alongside several canals. A strong image. Fall was inspired by this, although in a more minimalist shape. This exterior fixture is at a 10° angle and therefore seems to be bending slightly in the wind. The semi-transparent polycarbonate ensures diffused light. Available in various heights and colours. A ground stake is available for installation in soft ground.

Art. Nr. 11180832	
SPECIFICATIONS	
Lamp	1x LED-strip 24V 14.4W
Gear / Transfo	
Weight	3.6kg
Min. Distance	0.1 m
Power supply	230V
IP	IP54
Glow Wire Test	960°
Lifetime	40000 hrs
CRI	80
Lumen	335 Lm
Efficacy	16 Lm/W
UGR	18
Adjustability	Not Applicable
This luminaire contains built-in LED lamps. A** A ** A ** A ** A ** A ** B C D D E	This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf
The lamps cannot be changed in the luminaire.	

	WARM WHITE
	3000K / CRI 80+
black struc	11180832
white struc	11180809

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

FALL



4 LED GI		
FALL 1.1 IP54 LED GI ACCESSORIES		
EARTHPIN H350 WITH SQUARE PLATE 100X100	_	
•		
E	ARTHPIN H350 WITH SQUARE PLATE 100X100	