





LOTIS 86 IP55 LED RETROFIT

Lotis is the recessed spotlight which started it all. The hallmark of this luminaire, is the deeply recessed cone which holds the light source and has a fine edge. Lotis comes in different diameters and with different lighting sources. Lotis 48 is particularly fitted to use in wall mounted application.

| PECIFICATIONS | |
|---|--|
| Lamp | 1x LED Gu10 5.5W |
| Gear / Transfo | dimmable |
| Cut-out size | ø 79 h 135 |
| Weight | 0.45kg |
| Min. Distance | 0.1 m |
| Power supply | 230V |
| IP | IP55 |
| Glow Wire Test | 960° |
| Lifetime | 40000 hrs |
| CRI | 90 |
| Lumen | 339 Lm |
| Efficacy | 62 Lm/W |
| UGR | 9 |
| Adjustability | Not Applicable |
| This luminaire is compatible with bulbs of the energy classes: A** A** A** B** C** D** The luminaire is sold with a bulb of the energy class: A** A** A** A** B** C** B** A** A | This label is available in other languages: http://supermodular.com/assets/TYPE1.pdf |

CO RL +

| | WARM WHITE 2700K / CRI 90+ |
|-------------|-------------------------------|
| | MEDIUM 25° |
| alu struc | 11456228 |
| black struc | 11456208 |
| white struc | 11456238 |

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

LOTIS



| LOTIS 86 IP55 LED RETROFIT | | |
|----------------------------|----------------------|--|
| ACCESSORIES | | |
| GYPKIT | | |
| 12290230 | GYPKIT 190X190 - Ø80 | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |