


REKTOR RECESSED LED GE

Rektor, the surface-mounted spotlight by Modular, will guide the way around your space. Rektor is a surprising fixture, as it is highly directional despite the super-sleek housing. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Rektor is very versatile in use, as it can also be mounted on the MP78 light line. Recently launched Rektor recessed is nothing more, but also nothing less, than a highly adjustable ceiling spotlight. Pure essence of lighting.

Art. Nr. 12822032

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 65 h 70	
Weight	0.74kg	
Min. Distance	0.1	
IP	IP20	
Glow Wire Test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
Power supply	350mA	500mA
	31Vf	33Vf
Connected load	11W	16.25W
Lumen	777lm	1065lm
Efficacy	71lm/W	66lm/W
UGR	22	23
Adjustability	h 360° v -90°/+90°	



This label is available in other languages:
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	12821032	12821132	12822032	12822132
white struc	12821009	12821109	12822009	12822109

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

REKTOR RECESSED LED GE

ACCESSORIES

HUE-DEVICE

70000615	PHILIPS HUE TAP SWITCH
70000614	PHILIPS HUE DIMMER SWITCH
70000847	PHILIPS HUE SENSOR

HUE-BRIDGE

70000616	PHILIPS HUE BRIDGE EU
70000617	PHILIPS HUE BRIDGE UK

HUE-MODULE

13190030	MODULAR CONNECTED 1-10V WHITE COMPONENT
----------	---

CONBOX

10490330	CONBOX 112X172X100X236
----------	------------------------

GYPKIT

12291330	GYPKIT 170X112 - Ø65
----------	----------------------

