





WINK ASY 115 LED SPREADLIGHT GE

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. With the debut of the Wink 82, we are also presenting a completely new Wink accessory: Wink flange. Compatible with all 3 Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless install. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling.

Art. Nr. 13072009

SPECIFICATIONS

Lamp	1x LED Array		
Gear / Transfo	LED gear not incl.		
Cut-out size	ø 146 h 100		
Weight	0.86kg		
Min. Distance	0.1 m		
IP	IP54		
Glow Wire Test	960°		
CRI	90		
Power supply	350 mA	500mA	700mA
	29.1 Vf	29.9Vf	31 Vf
Connected load	11 W	16.2W	23.4W
Lumen	791Im	1042Im	1307lm
Efficacy	721m/W	65lm/W	571m/W
UGR	29	30	31
Adjustability	h 355°		
Remark	! 3500K and 4000K on request		

! must be used with recessed ring or flange



This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black struc	13071932	13072032
white struc	13071909	13072009













WINK ASY 115 LED SPREADLIGHT GE

O	v	3	×	Ľ	"	ч	3

HUE-DEVICE

 70000847
 PHILIPS HUE SENSOR

 70000615
 PHILIPS HUE TAP SWITCH

 70000614
 PHILIPS HUE DIMMER SWITCH

HUE-BRIDGE

70000617	PHILIPS HUE BRIDGE UK
70000616	PHILIPS HUE BRIDGE EU

HUE-MODULE

13190030 MODULAR CONNECTED 1-10V WHITE COMPONENT

RECESSED-FRAME

13073009	WINK 115 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)
13073032	WINK 115 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)
14204030	RECESSED RING Ø146 (FALSE CEILINGS)



