



ASY LOTIS 82 FOR LED GE

Lotis is known for its effortless design and high functionality. Asy lotis has all the features of a normal Lotis family member but has one additional benefit: assymetry. The light shines down at an angle of 28°, which creates an attractive wash effect on the wall. Available in different sizes, colours and variants (directional or non-directional). Asy lotis completes the full range of the Lotis family and blends perfectly with the other members of the family in the same space. Asy lotis 48 is the smallest member of the family noted for its deeply recessed lighting souce in the charasteristic cone.

Art. Nr. 13080209

SPECIFICATIONS

Lamp	1x LED (not incl.)
Gear / Transfo	LED gear not incl.
Cut-out size	ø 76 h 95
Weight	0.13kg
Min. Distance	0.1 m
Power supply	
IP	IP20
Glow Wire Test	960°
Adjustability	Not Applicable
Remark	! must be used with M-LED 50

alu	13080205
black	13080202
white struc	13080209



ASY LOTIS 82 FOR LED GE

ACCESSORIES

CONBOX

10889830 | CONBOX 190X192X130X256

GYPKIT

12290830 | GYPKIT 190X190 - Ø76

HUE-DEVICE

70000615 | PHILIPS HUE TAP SWITCH
70000847 | PHILIPS HUE SENSOR
70000614 | PHILIPS HUE DIMMER SWITCH

M-LED

14061105 | M-LED 50 4000K FLOOD GE ALU
14060905 | M-LED 50 4000K SPOT GE ALU
14060805 | M-LED 50 3500K FLOOD GE ALU
14060705 | M-LED 50 3500K MEDIUM GE ALU
14060605 | M-LED 50 3500K SPOT GE ALU
14061005 | M-LED 50 4000K MEDIUM GE ALU
14060505 | M-LED 50 3000K FLOOD GE ALU
14060405 | M-LED 50 3000K MEDIUM GE ALU
14060305 | M-LED 50 3000K SPOT GE ALU
14060205 | M-LED 50 2700K FLOOD GE ALU
14060105 | M-LED 50 2700K MEDIUM GE ALU
14060005 | M-LED 50 2700K SPOT GE ALU

LENSES

10212803 | SPREADLENS Ø44
10213103 | SOFTLENS Ø44

HUE-BRIDGE

70000617 | PHILIPS HUE BRIDGE UK
70000616 | PHILIPS HUE BRIDGE EU

HUE-MODULE

