

K72 IP55 LED TRE DIM RG


K already earned its spurs in the Modular range. With the LED dedicated rework of the K we honour an icon. A timeless product that will remain in the Modular portfolio for many years to come. Suitable for general and accent lighting, K is available in donkey grey and white structure.

Art. Nr. 14041509

SPECIFICATIONS

Lamp	1x LED Array 9.2W
Gear / Transfo	LED gear incl.
Cut-out size	ø 65 h 60
Weight	0.29kg
Min. Distance	0.1
Power supply	230V
IP	IP55
Glow Wire Test	960°
CRI	90
Lumen	712 Lm
Efficacy	59 Lm/W
UGR	21
Adjustability	Not Applicable
Remark	! 3500K on request

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	14041032	14041132	14041232	14041332	14041432	14041532	14041632	14041732	14041832
donkey grey struc	14041071	14041171	14041271	14041371	14041471	14041571	14041671	14041771	14041871
white struc	14041009	14041109	14041209	14041309	14041409	14041509	14041609	14041709	14041809



This label is available in other languages:
<http://supemodular.com/assets/TYPE2.pdf>

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

K72 IP55 LED TRE DIM RG

ACCESSORIES

GYPKIT

12291330 | GYPKIT 170X112 - Ø65

CONBOX

10490330 | CONBOX 112X172X100X236

