





## M-LED 50 GE

After introducing the M-LED 111 and M-LED 70 modules, Modular has again prepared some icons to be LED-ified. Replacing the well-known MR16 lamp, the M-LED 50 module is designed for Lotis for LED, Asy lotis for LED and Lotis square for LED. M-LED 111 is your solution for the Haloscan for LED and Multiple (trimless) for LED series, while M-LED 70 seamlessly fits your Mini multiple (trimless) for LED.

## Art. Nr. 14060805 SPECIFICATIONS 1x LED Array Lamp Gear / Transfo LED gear not incl. Weight 0.14kg Min. Distance ΙP IP20 Glow Wire Test 90 Power supply 350 mA 500mA 17.8Vf 18.4Vf Connected load 6.2W 9.2W 768lm Lumen 571lm Efficacy 921m/W 83lm/W UGR 20 22 Adjustability Not Applicable Remark ! can be combined with Lotis, Asy Lotis and Lotis square This label is available in other languages: MODULAR. http://supermodular.com/assets/TYPE2.pdf

											The lamps canno	<u>t</u> be
W	ARM WHIT	Е	W	ARM WHIT	Ë	N	EUTRAL W	/HITE	NEU	TRA	CANADALE in the In	ıminaire.
270	00K / CRI 9	0+	300	00K / CRI 9	+00	3	500K / CR	190+	400	0K/	CRI 90+	
SPOT	MEDIUM	FLOOD	SPOT	MEDIUM	FLOOD	SPOT	MEDIUM	FLOOD	SPOT	MED	I lettrat/e offite.OOD	
15°	25°	40°	15°	25°	40°	15°	25°	40°	15°	25	\$40°	$\sim$
14060005	14060105	14060205	14060305	14060405	14060505	14060605	14060705	14060805	14060905	1406	100514061105	<b>→</b> Ì
	270 SPOT 15°	2700K / CRI 9  SPOT MEDIUM 15° 25°	15° 25° 40°	2700K / CRI 90+ 300  SPOT MEDIUM FLOOD SPOT 15° 40° 15°	2700K/CRI 90+ 3000K/CRI 5 SPOT MEDIUM FLOOD SPOT MEDIUM 15° 25° 40° 15° 25°	2700K / CRI 90+     3000K / CRI 90+       SPOT 15°     MEDIUM 25°     FLOOD 40°     SPOT 25°     MEDIUM 25°     FLOOD 40°	2700K / CRI 90+ 3000K / CRI 90+ 3  SPOT MEDIUM FLOOD SPOT MEDIUM FLOOD SPOT 15° 25° 40° 15° 40° 15°	2700K / CRI 90+         3000K / CRI 90+         3500K / CR           SPOT 15°         MEDIUM 15°         FLOOD 15°         SPOT 25°         MEDIUM 15°         FLOOD 25°         MEDIUM 25°<	2700K / CRI 90+         3000K / CRI 90+         3500K / CRI 90+           SPOT 15°         MEDIUM 25°         FLOOD 40°         SPOT 40°         MEDIUM 50°         FLOOD 50°         SPOT 40°         MEDIUM 50°         FLOOD 25°         40	2700K / CRI 90+         3000K / CRI 90+         3500K / CRI 90+         400           SPOT 15°         MEDIUM 25°         FLOOD 15°         SPOT 40°         MEDIUM 15°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         MEDIUM 15°         SPOT 40°         MEDIUM 15°         MEDIUM 15°	2700K / CRI 90+         3000K / CRI 90+         3500K / CRI 90+         400 K /           SPOT 15°         MEDIUM 25°         FLOOD 3POT 40°         SPOT 40°         MEDIUM 5FLOOD 3POT 40°         MEDIUM 5FLOOD 3POT 40°         MEDIUM 5FLOOD 3POT 40°         MEDIUM 5FLOOD 3POT 40°         MEDIUM 15°         MEDIUM 25°         40°         15°         <	WARM WHITE         WARM WHITE         NEUTRAL WHITE

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

## M-LED



M-LED	50	GE	
-------	----	----	--