





ESSELDI EYEBALL SUSPENSION LED DOWN GI

Modular launched its new SLD50 profile range almost a year ago, and it proved to be an instant hit. Esseldi takes this iconic thin, linear lighting profile even further in the form of two lengths: 1147 mm and 1920 mm. Select a surface-mounted installation with a downwards light effect, or a suspended installation with a downward or up/down light effect.

Art.Nr. 93560018 SPECIFICATIONS		
Gear / Transfo	LED gear incl.	
Weight	7.65kg	
Min. Distance	0.1 m	
Power supply	230V	
IP	IP20	
Glow Wire Test	850°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
Lumen	3251 Lm	
Efficacy	68 Lm/W	
UGR	24	
Adjustability	Not Applicable	
MODULAR This luminaire contains built-in LED lamps. ATA ATA B C D E The lamps cannot be changed in the luminaire.	This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf	
874/2012	<u> </u>	

	WARM WHITE 2700K / CRI 90+
	MEDIUM 25°
black struc	93560019
white struc	93560018

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.