

TECHNICAL INFORMATION

UNA BRANCO 15W 3000K

Downlight com temperatura de luz de 4000K, design elegante, lente opal para um desempenho superior e alta proteção (IP54).

Versatile Dimmable Downlight with color temperature 4000K, stylish design, opal lens for superior performance and high protection (IP54).

Downlight con temperatura de la luz 4000K, diseño elegante, lente opal para un rendimiento superior y alta protección (IP54).




ILAR-01000


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01000	Length	Ø145mm	Total Luminous Flux	1560lm
LED Brand	Sanan	Width	-	Luminous Efficacy	105lm/w
Mounting Type	Recessed	Height	45mm	Beam Angle	90°
Body Material	Aluminium	Weight	0.81	Colour Temperature	3000K
Housing Colour	White RAL9016	Cutout	Ø120-130mm	Colour Rendering Index	>80
Body Shape	Round	Packaging Unit	10pcs/carton	Colour Consistency	≤6
Nominal Lifetime (EOL end of life)	50.000H	Gross Weight	10.5kg	UGR	<21
Dimmable	YES				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	15W	Energy Label	-	2014/30/EU (EMC Directive)	YES
Nominal Voltage	200-240V	Energy Consumption KWH/1000H	-	2014/35/EU (LVD Directive)	YES
Operating Frequency	50Hz	Type of Protection	IP54	ROHS	YES
Power Factor	≥0.9	Protection Class	Class II	Warranty	3 YEARS
Operating Temperature	-20°C to +45°C	Protection Class IK (shock resistance)	IK03		
Starting Time 100% ON	0.0001s				
ON/OFF Cycles	100.000				

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

