

TECHNICAL INFORMATION

HIGHBAY LINEAR LUMIA

200W 5000K

Nova linha de campânulas lineares, IP66, IK08, ccom design moderno e alta eficácia (160lm/W).

New line of linear highbays, IP66, IK08, with modern design and high efficiency (160lm/W).

Nueva línea de campanas lineales, IP66, IK08, de diseño moderno y alta eficiencia (160lm/W).



ILAR-02153

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-02153	Dimensions	1192x105x79mm	Total Luminous Flux	32000lm
Led Type	Philips SMD	Packaging Unit	1 pcs	Luminous Efficacy	160lm/W
Body Material	Pure AL A6063(226W/m.K)	Weight (kg)	2,4kg	Beam Angle	60x110°
Lens Material	PC			Colour Temperature	5000K
Housing Colour	White			Colour Rendering Index	>80
Mounting Type	Bracket/Suspended				
Sensor	Optional				
Dimmable	Optional(1-10V, DALI)				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	200W	Type of Protection(IP)	IP66	CE	YES
Nominal Voltage	AC100-277V	Protection Class	Class I	ROHS	YES
Operating Frequency	50-60Hz	Shock resistance (IK)	IK08	Warranty	5 YEARS
Power Factor	>0.95	Surge Protection	4kV		
Operating Temperature	-25°C to + 45°C				
Life time	(L90B10): 50000H				
Linkable	Yes				

SIZE	PHOTOMETRY	ACCESSORIES
		Suspension Kit 1.1m ILAR-02154 Adjustable Wall Bracket ILAR-02155

Designed by Aron Light in Portugal Made in PRC

