




BOULY C50 DOWN



Material	Materiaal	Matériau
aluminium - PMMA	aluminium - PMMA	aluminium - PMMA
Finish	Afwerking	Finition
black - chrome - gold - grey - ivory - white PMMA : transparent lens : PMMA	zwart - chroom - goud - grijs - ivoor - wit PMMA : transparent lens : PMMA	noir - chrome - or - gris - ivoire - blanc PMMA : transparent lentille : PMMA
Lightsource	Lichtbron	Source lumineuse
4 x power LED (included) 1.2W cold white : 6000K - 440lm - CRI >75 4 x LED (included) 0.96W warm white : 2700K - 456lm - CRI >93 beam : 10° - 25° - 40°	4 x power LED (inclusief) 1.2W koud wit : 6000K - 440lm - CRI >75 4 x LED (inclusief) 0.96W warm wit : 2700K - 456lm - CRI >93 lichtbundel : 10° - 25° - 40°	4 x power LED (inclus) 1.2W blanc froid : 6000K - 440lm - CRI >75 4 x LED (inclus) 0.96W blanc chaud : 2700K - 456lm - CRI >93 rayon de lumière : 10° - 25° - 40°
Connection	Aansluiting	Connexion
350mA - driver excluded	350mA - voeding exclusief	350mA - convertisseur exclus
Specifications	Specificaties	Spécifications
indoor ceiling mounting class III IP40	binnen plafondmontage klasse III IP40	intérieur plafonnier classe III IP40
Optional	Optioneel	Option
LED driver max. 4 x 0.96W to build in, not dimmable 42 x 40 x 22 mm	LED voeding max. 4 x 0.96W inbouw, niet dimbaar 42 x 40 x 22 mm	LED convertisseur max. 4 x 0.96W encastré, non-dimmable 42 x 40 x 22 mm

