



Small, fine, elegant and discreet - The ACAMAR is a light manufactured from high-quality aluminium. The colour reproduction value is over 90, which means high colour authenticity. The design is chic and attractive thanks to its curvature on one side. You can mount the light with the curvature upwards or downwards, depending on your preference. The white paint inside accentuates the warm white light and ensures pleasant scattering upwards and downwards. The outside is highly polished for an incredible shine.

<b>Housing Material</b>	Aluminium	<b>Storage Temperature</b>	-10 to 60 °C
<b>Housing Color</b>	Black	<b>IP Protection Class</b>	IP 20
<b>Protection Class</b>	Protection class I/protective grounding	<b>Life Time L70 / B50</b>	30000 h
<b>Rated Input</b>	6.9 W	<b>Switching Cycles</b>	100000
<b>Rated Power Consumption Standby</b>	0.5 W	<b>Power Consumption</b>	7 kWh/1000h
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>EEL</b>	G
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	300 lm		
<b>Rated Angle of Reflection</b>	105 Degree		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Length</b>	170 mm		
<b>Width</b>	100 mm		
<b>Height</b>	80 mm		
<b>Base length</b>	120 mm		
<b>Base width</b>	60 mm		
<b>Base height</b>	33 mm		
<b>Working Temperature</b>	-5 to 40 °C		