



The elegant APODIS wall light captivates with its high-quality aluminium housing with compact base and a fine two-colour coating in black and gold. The Apodis emits powerful warm white light both upwards and downwards via the double light output. The light can be dimmed flexibly using leading/trailing phase angles.

<b>Housing Material</b>	Aluminium	<b>Working Temperature</b>	-5 to 40 °C
<b>Housing Color</b>	Rosé, Black	<b>Storage Temperature</b>	-10 to 60 °C
<b>Protection Class</b>	Protection class I/protective grounding	<b>IP Protection Class</b>	IP 20
<b>Rated Input</b>	14.7 W	<b>Life Time L70 / B50</b>	25000 h
<b>Rated Power Consumption Standby</b>	0.5 W	<b>Switching Cycles</b>	100000
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>Power Consumption</b>	15 kWh/1000h
<b>Power Supply Unit incl.</b>	Yes	<b>EEL</b>	G
<b>Dimmable</b>	Yes		
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour consistency light source</b>	6 SDCM		
<b>CRI (Ra)</b>	80		
<b>Rated Luminous Flux</b>	450 lm		
<b>Rated Angle of Reflection</b>	30 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Top, Below		
<b>Length</b>	76 mm		
<b>Width</b>	61 mm		
<b>Height</b>	800 mm		
<b>Base length</b>	60 mm		
<b>Base width</b>	18 mm		
<b>Base height</b>	100 mm		