



The BRAHE wall light with gooseneck and narrow light emission angle of 25° means anyone else in the bed can sleep peacefully while the person on the other side is still reading. The simple design of the BRAHE also impresses in other areas, such as reading nooks.

Special features

- High-quality, flexible gooseneck
- Gooseneck with silicone sleeve for easy cleaning
- Individually adjustable via flexible gooseneck
- Ideal for use as a reading light

Housing Material	Aluminium	IP Protection Class	IP 20
Housing Color	Black		
Protection Class	Protection class II/protective insulation	Life Time L70 / B50	30000 h
Rated Input	3.3 W	Switching Cycles	100000
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz	Power Consumption	4 kWh/1000h
Power Supply Unit incl.	Yes	EEI	G
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	165 lm		
Rated Angle of Reflection	25 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Swivel Angle	360 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	310 mm		
Height	80 mm		
Diameter	25 mm		
Base length	80 mm		
Base width	80 mm		
Base height	25 mm		
Working Temperature	0 to 60 °C		
Storage Temperature	0 to 60 °C		