



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

Special features

- Light colour adjustable in two stages
- Circumferential diffuser
- Can be suspended by up to 1,800/3,000 mm [depending on model]

Housing Material	Aluminium	Working Temperature	-10 to 45 °C
Housing Color	Black	Storage Temperature	-10 to 45 °C
Surface structure	Matt	IP Protection Class	IP 20
Material of Lens	Acryl	IK Protection Class	IK04
Surface Structure of Lens	Satined		
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	30000 h
Rated Input	60 W	Switching Cycles	20000
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Power Consumption	60 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class F.
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	4100/4200 lm		
Rated Angle of Reflection	150 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	110 mm		
Diameter	800 mm		
Base height	65 mm		
Base diameter	275 mm		
Pendulum Length max.	3000 mm		