



The pendant lamps of the MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 380, 580 and 780 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The exterior finish is brushed aluminium in the colours coffee and silver or matt powder-coated in black and white.

Special features

- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]

Housing Material	Aluminium
Housing Color	White
Surface structure	Matt
Material of Lens	Acryl
Surface Structure of Lens	Satined
Protection Class	Protection class I/protective grounding
Rated Input	30 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Storage Temperature	-10 to 45 °C
IP Protection Class	IP 20
IK Protection Class	IK04

Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	30 kWh/1000h
Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class E.

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2100/2200 lm
Light Distribution	Symmetric

Light Exit Surfaces	1
Light characteristics	Direct, Indirect
Light direction	Top, Below

Height	35 mm
Diameter	380 mm
Base height	65 mm
Base diameter	220 mm
Pendulum Length max.	1800 mm

Working Temperature	-10 to 45 °C
----------------------------	--------------

