




The pendant lamps of the MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 380, 580 and 780 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The exterior finish is brushed aluminium in the colours coffee and silver or matt powder-coated in black and white.

Special features

- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]

Housing Material	Aluminium	IP Protection Class	IP 20
Housing Color	Silver	IK Protection Class	IK04
Surface structure	Brushed		
Material of Lens	Acryl		
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	30000 h
Rated Input	30 W	Switching Cycles	20000
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Power Consumption	30 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	2100/2200 lm		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	35 mm		
Diameter	380 mm		
Base height	65 mm		
Base diameter	220 mm		
Pendulum Length max.	1800 mm		
Working Temperature	-10 to 45 °C		
Storage Temperature	-10 to 45 °C		

