



The pendant lamps of the MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 380, 580 and 780 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The exterior finish is brushed aluminium in the colours coffee and silver or matt powder-coated in black and white.

#### Special features

- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]

|  |   |  |  |
|--|---|--|--|
| <b>Housing Material</b>                | Aluminium                                 | <b>IP Protection Class</b>                 | IP 20  |
| <b>Housing Color</b>                   | Silver                                    | <b>IK Protection Class</b>                 | IK04   |
| <b>Surface structure</b>               | Brushed                                   |  |  |
| <b>Material of Lens</b>                | Acryl                                     | <b>Life Time L70 / B50</b>                 | 30000 h  |
|  |   | <b>Switching Cycles</b>                    | 20000  |
| <b>Protection Class</b>                | Protection class I/protective grounding   | <b>Power Consumption</b>                   | 60 kWh/1000h   |
| <b>Rated Input</b>                     | 60 W                                      | <b>Energy Efficiency Class Lightsource</b> | This product contains a light source of energy efficiency class F. |
| <b>Rated Input Voltage Frequency</b>   | 220-240 V/AC 50 / 60 Hz                   |  |  |
| <b>Power Supply Unit incl.</b>         | Yes                                       |  |  |
| <b>Dimmable</b>                        | Yes                                       |  |  |
| <b>Control</b>                         | Leading-edge dimmer, Trailing-edge dimmer |  |  |
| <b>Motion Detector</b>                 | No  |  |  |
| <b>Light Source</b>                    | LED, Light source changeable TC           |  |  |
| <b>Color Temperature</b>               | 3000/4000 K                               |  |  |
| <b>Colour Consistency</b>              | 6 SDCM                                    |  |  |
| <b>Colour consistency light source</b> | 6 SDCM                                    |  |  |
| <b>Colour Rendering Index (Ra)</b>     | 80  |  |  |
| <b>Rated Luminous Flux</b>             | 4800/4900 lm                              |  |  |
| <b>Light Distribution</b>              | Symmetric                                 |  |  |
| <b>Light Exit Surfaces</b>             | 1   |  |  |
| <b>Light characteristics</b>           | Direct, Indirect                          |  |  |
| <b>Light direction</b>                 | Top, Below                                |  |  |
| <b>Height</b>                          | 35 mm                                     |  |  |
| <b>Diameter</b>                        | 780 mm                                    |  |  |
| <b>Base height</b>                     | 65 mm                                     |  |  |
| <b>Base diameter</b>                   | 275 mm                                    |  |  |
| <b>Pendulum Length max.</b>            | 3000 mm                                   |  |  |
| <b>Working Temperature</b>             | -10 to 45 °C                              |  |  |
| <b>Storage Temperature</b>             | -10 to 45 °C                              |  |  |

