



MENKAR series pendant lamps feature clever lighting functions and high-quality aluminium accents. The rear light, which can be switched on separately (approx. 15-20 % of indirect lighting component), allows continuous indirect lighting whilst the main light can be switched on at any time.

Special features

- Indirect and direct lighting
- High light intensity
- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]
- Optional diffuser lens for UGR<19

| | |
|--------------------------------------|---|
| Housing Material | Aluminium |
| Housing Color | Silver |
| Surface structure | Brushed |
| Material of Lens | Acryl |
| Protection Class | Protection class I/protective grounding |
| Rated Input | 45 W |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | Yes |
| Dimmable | Yes |
| Control | Leading-edge dimmer, Trailing-edge dimmer |
| Motion Detector | No |

| | |
|---|---|
| IP Protection Class | IP 20 |
| IK Protection Class | IK04 |
| Life Time L70 / B50 | 30000 h |
| Switching Cycles | 20000 |
| Power Consumption | 45 kWh/1000h |
| Energy Efficiency Class Lightsources | This product contains light sources of energy efficiency classes E and F. |

| | |
|--|---------------------------------|
| Light Source | LED, Light source changeable TC |
| Color Temperature | 3000/4000 K |
| Colour Consistency | 6 SDCM |
| Colour consistency light source | 6 SDCM |
| Colour Rendering Index (Ra) | 80 |
| Rated Luminous Flux | 3300/3500 lm |
| Light Distribution | Symmetric |

| | |
|------------------------------|------------------|
| Light Exit Surfaces | 2 |
| Light characteristics | Direct, Indirect |
| Light direction | Top, Below |

| | |
|-----------------------------|---------|
| Height | 90 mm |
| Diameter | 400 mm |
| Base height | 30 mm |
| Base diameter | 100 mm |
| Pendulum Length max. | 1800 mm |

| | |
|----------------------------|--------------|
| Working Temperature | -10 to 45 °C |
| Storage Temperature | -10 to 45 °C |

