




MENKAR series pendant lamps feature clever lighting functions and high-quality aluminium accents. The rear light, which can be switched on separately (approx. 15-20 % of indirect lighting component), allows continuous indirect lighting whilst the main light can be switched on at any time.

Special features

- Indirect and direct lighting
- High light intensity
- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]
- Optional diffuser lens for UGR<19

Housing Material	Aluminium
Housing Color	Coffee
Surface structure	Brushed
Material of Lens	Acryl
Protection Class	Protection class I/protective grounding
Rated Input	45 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

IP Protection Class	IP 20
IK Protection Class	IK04
Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	45 kWh/1000h
Energy Efficiency Class Lightsources	This product contains light sources of energy efficiency classes E and F.

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	3300/3500 lm
Light Distribution	Symmetric

Light Exit Surfaces	2
Light characteristics	Direct, Indirect
Light direction	Top, Below

Height	90 mm
Diameter	400 mm
Base height	30 mm
Base diameter	100 mm
Pendulum Length max.	1800 mm

Working Temperature	-10 to 45 °C
Storage Temperature	-10 to 45 °C

