



Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.

Special features

- Can be rotated and swivelled via joints
- Dimmable in three stages using touch sensor

Housing Material	Aluminium	Base height	21.5 mm
Housing Color	White	Base diameter	180 mm
Material of Lens	Plastic	Product weight	2388 g
Protection Class	Protection class II/protective insulation	Working Temperature	-5 to 40 °C
Rated Input	12 W	Storage Temperature	-20 to 50 °C
Rated Power Consumption Standby	0.5 W	IP Protection Class	IP 20
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz	Life Time L70 / B50	25000 h
Power Supply Unit incl.	Yes	Switching Cycles	12500
Connection Cable Primary	Yes	Power Consumption	12 kWh/1000h
Primary Connection	Power plug	EEI	G
Primary Cable Length	1.6 m		
Dimmable	Yes		
Control	Touch-Sensor		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	950 lm		
Luminous Efficiency	79.2 lm/W		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	DLS		
Swivel Angle	180 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	498 mm		
Height	480 mm		
Diameter	150 mm		