



Discover our portable cordless LED lamps from the CANIS series. With a 2.3 W output and 110 lm of brightness, our lamps provide a particularly wide and pleasant light distribution. And the infinitely variable dimming function allows you to set the perfect illumination using the practical touch sensor. Choose from two light colour levels to create the perfect atmosphere. And the best part? One battery charge is enough for more than eight hours of lighting. You can charge up to 15 lamps at the same time with the optional charging station, so you always have enough lights to hand. Choose from eight colours, including trendy pastel tones, to reflect your personal style.

#### Special features

- Pleasant and wide light distribution
- More than eight hours of light after charging
- Infinitely dimmable via touch sensor
- Light colour adjustable in two stages
- charge up to 15 cordless lights at the same time using the stackable charging dock (optional)
- USB charging base not included in the scope of delivery (optional)

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Green
<b>Surface structure</b>	Matt
<b>Material of Lens</b>	Polycarbonate - PC
<b>Surface Structure of Lens</b>	Clear
<b>Functions</b>	Nightsaver

<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Rated Input</b>	2.3 W
<b>Rated Input Voltage</b>	3.7 V/DC
<b>Dimmable</b>	Yes
<b>Control</b>	Touch-Sensor
<b>Motion Detector</b>	No
<b>Accumulator/Battery Operated</b>	Yes
<b>Rechargeable/battery included</b>	Yes
<b>Number of Accumulator/Battery</b>	1 PCS
<b>Type of Accumulator/Battery</b>	3.7 V lithium ion battery (903050)
<b>Accumulator/Battery Capacity</b>	3000 mAh
<b>Accumulator/Battery Voltage</b>	3.7 V
<b>Accumulator Charging Time</b>	4.5 h
<b>Accumulator Operating Time</b>	8 h

<b>Light Source</b>	LED, Light source changeable TC
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	2200/3000 K
<b>CRI (Ra)</b>	80
<b>Rated Luminous Flux</b>	110 lm
<b>Luminous Efficiency</b>	47.8 lm/W

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	208 mm
---------------	--------

<b>Diameter</b>	76 mm
<b>Product weight</b>	345 g
<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-20 to 50 °C
<b>IP Protection Class</b>	IP 65
<b>IK Protection Class</b>	IK04

<b>Life Time L70 / B50</b>	20000 h
<b>Power Consumption</b>	3 kWh/1000h