



It takes a lot to catch the Altais series off guard. Thanks to IP54 and impact strength class IK10, these slender outdoor lamps are impressive all-rounders both in commercial and private settings. Altais Motion lamps offer additional versatility with their integrated motion sensor (programmable using supplied remote control) and the adjustable light colour for different lighting scenarios.

Special features

- Light colour adjustable in three steps
- Optional surface-mounted cable entry
- Feed-through wiring possible
- Motion detector can be adjusted by remote control (in scope of delivery)

Housing Material	Plastic
Housing Color	White
Halogen free	Yes
Protection Class	Protection class II/protective insulation
Rated Input	12 W
Rated Power Consumption	0.5 W
Network Standby	
Rated Input Voltage	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	1-12 m
Angle of Detection	150 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	No
Adjustable follow-up time	Yes
Follow-up time	5-600 s

Light Source	LED, Light source not changeable
Color Temperature	3000/4000/6000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	85
Rated Luminous Flux	1260 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	48 mm
Diameter	220 mm

Working Temperature	-40 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54
IK Protection Class	IK10
Life Time L70 / B50	50000 h
Switching Cycles	75000
Power Consumption	12 kWh/1000h
EEI	E

