



It takes a lot to catch the Altais series off guard. Thanks to IP54 and impact strength class IK10, these slender outdoor lamps are impressive all-rounders both in commercial and private settings. Altais Motion lamps offer additional versatility with their integrated motion sensor (programmable using supplied remote control) and the adjustable light colour for different lighting scenarios.

#### Special features

- Light colour adjustable in three steps
- Optional surface-mounted cable entry
- Feed-through wiring possible
- Motion detector can be adjusted by remote control (in scope of delivery)

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	White
<b>Halogen free</b>	Yes
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	18 W
<b>Rated Power Consumption</b>	0.5 W
<b>Network Standby</b>	
<b>Rated Input Voltage</b>	220-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	No
<b>Motion Detector</b>	Yes
<b>Kind of Motion Detector</b>	High frequency
<b>Detection Distance</b>	1-12 m
<b>Angle of Detection</b>	150 Degree
<b>Motion detector changeable</b>	Yes
<b>Adjustable brightness threshold</b>	No
<b>Adjustable follow-up time</b>	Yes
<b>Follow-up time</b>	5-600 s

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000/4000/6000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour consistency light source</b>	6 SDCM
<b>CRI (Ra)</b>	85
<b>Rated Luminous Flux</b>	1870 lm
<b>Rated Angle of Reflection</b>	120 Degree
<b>Distribution Characteristic 120°</b>	NDLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	48 mm
<b>Diameter</b>	280 mm

<b>Working Temperature</b>	-40 to 50 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 54
<b>IK Protection Class</b>	IK10
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	75000
<b>Power Consumption</b>	18 kWh/1000h
<b>EEL</b>	D

