



The UNI II series includes high-quality surface-mounted lamps for use on walls and ceilings in commercial and private spaces. The rotatable and swivelling lamp heads have warm white COB LEDs and, if required, can be folded flush to the mount to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple versions, there is both a mini version (with smaller lamp head and mount) and a MAX version available. There is also a version for use in current tracks.

#### Special features

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Black
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	20 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	Yes
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

<b>Base width</b>	20 mm
<b>Base height</b>	14 mm
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-20 to 50 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time L70 / B50</b>	20000 h
<b>Switching Cycles</b>	15000
<b>Power Consumption EEI</b>	20 kWh/1000h G

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour consistency light source</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	1440 lm
<b>Rated Angle of Reflection</b>	36 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	90 Degree
<b>Rotation Angle</b>	350 Degree
<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	212 mm
<b>Width</b>	100 mm
<b>Height</b>	103 mm
<b>Base length</b>	212 mm