



The ALWAID 2 recessed wall light fits into any 68 mm standard or deep switch box thanks to its compact design. Furthermore, it does not require an additional power supply. The variety of covers allows you to find a style that suits your space and illuminates your surroundings with beautiful indirect light. The article includes the base only; covers are not included in the scope of delivery.

#### Special features

- 230 V direct connection
- Feed-through wiring possible
- Can be dimmed using leading-edge phase dimmers or trailing-edge phase dimmers
- Suitable for 68 mm standard and deep switch boxes

<b>Housing Material</b>	Aluminium	<b>Switching Cycles</b>	50000
<b>Housing Color</b>	White	<b>Power Consumption</b>	5 kWh/1000h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Energy Efficiency Class Lightsources</b>	This product contains a light source of energy efficiency class G.
<b>Rated Input</b>	4.8 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control</b>	Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	3 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	215 lm		
<b>Luminous Efficiency</b>	44.8 lm/W		
<b>Rated Angle of Reflection</b>	100 Degree		
<b>UGR</b>	19		
<b>Height</b>	39.9 mm		
<b>Diameter</b>	71.2 mm		
<b>Installation Depth</b>	39.9 mm		
<b>Cut Out Diameter</b>	61.5 mm		
<b>Product weight</b>	71 g		
<b>Working Temperature</b>	-10 to 55 °C		
<b>Storage Temperature</b>	-60 to 20 °C		
<b>IP Protection Class</b>	IP 20		
<b>Life Time L70 / B50</b>	75000 h		
<b>Life Time L80 / B10</b>	50000 h		
<b>Life Time L80 / B50</b>	60000 h		

