



A spotlight with that certain something: Thanks to the acrylic ring, the COB 68 acrylic not only emits light downwards but also softly to the side. The resulting light pattern on the ceiling subtly yet effectively draws the eye and creates a cosy ambience that permeates each space.

Special features

- Ring made from acrylic glass
- Subtle side lighting
- Lamp can be disconnected via plug
- Acrylic rings can be replaced (optional)
- Incl. two diffusing lenses (transparent/satin-finished)

Housing Material	Aluminium	Length	78 mm
Housing Color	Silver	Height	53.5 mm
Material of Lens	PMMA	Diameter	78 mm
Protection Class	Protection class III/safety extra-low voltage	Installation Depth	50 mm
Operating Mode	Constant current	Cut Out Diameter	62 mm
Rated Input	6.8 W	Product weight	204 g
Rated Power Consumption Standby	0.5 W	Working Temperature	-5 to 40 °C
Rated Input Voltage	18-20 V/DC	Storage Temperature	-25 to 40 °C
Rated Current	350 mA	IP Protection Class	IP 20
Power Supply Unit incl.	No	Life Time L70 / B50	30000 h
Connection Cable Secondary	Yes	Switching Cycles	50000
Secondary Connection	Open cables	Power Consumption	7 kWh/1000h
Secondary Cable Length	0.3 m	EEI	G
Dimmable	Yes		
Control	Dimmable via optional power supply unit		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	2700 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	935 lm		
Luminous Efficiency	137.5 lm/W		
Rated Angle of Reflection	36 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		